

EV130 ventilates up to 2700 square feet of living space.

Specifications

Typical Airflow Range: 50-140 CFM				
ARI 1060 Certified Core: One L50*				
Number of Motors: One, 0.07 hp				
VAC	HZ	Phase	Input Watts	FLA
115	60	Single	124@ .4" esp.	1.1
Control Voltage: 24 VAC				
Connection Collars: Round; 6" & 8"				
Filters: Cleanable, spun polyester media. 10.5" x 21.75" x 1"				
Weight: 52 lbs. (unit), 57 lbs. (shipping weight)				
Shipping Dimensions: 21" W x 32" L x 15.5" H				

Performance

Airflow CFM	ESP in H ₂ O	Temp EFF%*	Total EFF% Winter/Summer*
35	0.80	84	74/57
71	0.70	80	70/51
95	0.60	76	66/45
111	0.50	75	65/44
118	0.40	74	64/43
127	0.30	73	63/42
131	0.20	73	62/41
140	0.10	72	61/40

HVI certified – see product literature for complete certified ratings.
*At ARI 1060 standard conditions.

EV200 ventilates up to 4000 square feet of living space.

Specifications

Typical Airflow Range: 100-200 CFM				
ARI 1060 Certified Core: One L100*				
Number of Motors: One, 0.1 hp				
VAC	HZ	Phase	Input Watts	FLA
115	60	Single	151@ .2" esp.	1.5
Control Voltage: 24 VAC				
Connection Collars: Round; 6" & 8"				
Filters: Cleanable, spun polyester media. 10.5" x 21.75" x 1"				
Weight: 80 lbs. (unit), 88 lbs. (shipping weight)				
Shipping Dimensions: 21" W x 32" L x 26.5" H				

Performance

Airflow CFM	ESP in H ₂ O	Temp EFF%*	Total EFF% Winter/Summer*
129	0.80	82	72/53
141	0.70	81	71/52
150	0.65	80	70/51
172	0.50	80	70/50
178	0.40	79	69/48
188	0.30	78	68/47
192	0.20	77	67/46
200	0.10	76	66/45

HVI certified – see product literature for complete certified ratings.
*At ARI 1060 standard conditions.

EV300 ventilates up to 6000 square feet of living space.

Specifications

Typical Airflow Range: 150-300 CFM				
ARI 1060 Certified Core: One L100*				
Number of Motors: One, 0.2 hp				
VAC	HZ	Phase	Input Watts	FLA
115	60	Single	300@ .4" esp.	3.3
Control Voltage: 24 VAC				
Connection Collars: Oval; 8" round compatible				
Filters: Cleanable, spun polyester media. 10.5" x 21.75" x 1"				
Weight: 86 lbs. (unit), 95 lbs. (shipping weight)				
Shipping Dimensions: 21" W x 32" L x 26.5" H				

Performance

Airflow CFM	ESP in H ₂ O	Temp EFF%*	Total EFF% Winter/Summer*
150	1.00	80	70/51
200	0.85	76	66/45
220	0.80	75	65/44
270	0.60	72	62/40
300	0.40	70	60/38
310	0.20	69	59/39
320	0.00	68	58/36

HVI certified – see product literature for complete certified ratings.
*At ARI 1060 standard conditions.



Distributed by Sound Geothermal Corporation

801-642-6100

ACCESSORIES:

- Percentage runtime control (2-wire) - PT24
- Fan interlock module (6-wire) - FM24
- Point of use control (push button) - PB24
- 24-hour timer control - TS24/120
- Dehumidistat control - DH24
- Wall caps: brown (VB106) or white (VW106)